



# STYLE FGT WOVEN TEXTURISED FIBREGLASS TAPE

Fibreglass | Woven

## FEATURES

Style FGT is fibreglass fibres woven into tape form. It is user friendly in so much as particle emission is minimized due to process, therefore reducing the chance of irritability when being applied in the workplace. It does not shrink with atmospheric changes.

Fibreglass tapes are resistant to oils, solvents and most chemicals, but direct contact with live steam should be avoided.

## TECHNICAL INFORMATION

Construction	Woven
Weight	3.0mm (1900g/sq/m) 1.5mm (1000g/sq/m)
Temperature	538°C (1000°F)
Colour	White
MSDS	Available upon request

## AVAILABLE SIZES

**WIDTH/RANGE** 25mm - 150mm x 3mm & 1.5mm thick

**ROLL LENGTH** 30m (standard)

Other sizes available upon request.

Available with coatings/finishes:

- > Laminated
- > Aluminium faced
- > Graphite impregnated (black)
- > Red silicone coated on one side



## APPLICATIONS

The tape will not support combustion or burn. It is unaffected by most dilute alkalis and acids. Usual applications include:

- > Thermal & Electrical insulation wrap
- > Gasket Seals
- > Welding Blankets
- > Lagging on pipe work
- > Installation and Expansion Joints

It is unaffected by weather or moisture.