

MP1890F

Ramie Fibre Packing | Inter-braided | Impregnated with PTFE & Silicon Oil

FEATURES

MP1890F is a long ramie fibre which is square and thoroughly impregnated with mineral grease and PTFE (or tallow) to make the packing pliable and resilient. A very white packing suited to use in the mid range of pH.

TECHNICAL INFORMATION

Construction	Inter-braided
pH Value	5 – 9
Temperature	-50°C to +140°C
Pressure	150Psi (1050Kpa)
Speed	2000 FPM (10m/sec)
Colour	White
MSDS	Available upon request

AVAILABLE SIZES

STANDARD THICKNESS

8m rolls

STANDARD ROLL SIZE

 $3mm\ x\ 3mm\ through$ to $25mm\ x\ 25mm$

Cut lengths, strips and custom shapes are available upon request Larger coils & sizes available upon request



APPLICATIONS

MP1890F is ideally suited for use in the less demanding applications. It can service:

- > Pumps
- > Valves
- > Plungers
- > Seal hot and cold water and brine

It is especially suitable for marine use. It is also suitable for use in oils and solvents. This packing has a good resistance to: mildew, fungi and bacteria. Suitable for rotary, reciprocating and static service.

www.industrialgaskets.com.au

Whilst every effort has been made to supply accurate information this specification should be used as a guide only. IG reserves the right to make specification changes without notice or without incurring liability.

Industrial Gaskets | Compression Packing

E sales@industrialgaskets.com.au

P (08) 8276 4140