



MP4130

Pure PTFE Packing | Inter-braided | Food Grade

FEATURES

MP4130 is a pure PTFE fibre inter-braided into a deformable square packing. A clean packing capable of handling the full pH range. It remains soft and flexible throughout service with negligible water absorption. It is non-toxic and ideally suited for food and drink industry. Conforms to FDA requirements. Also available Lubricated (L) with silicon oil to enhance pump start up.

TECHNICAL INFORMATION

Construction	Inter-braided
pH Value	0 – 14
Temperature	-268°C to +260°C
Pressure	500Psi (3500Kpa) in dynamic service
Speed	1575 FPM (8m/sec)
Colour	White
MSDS	Available upon request

AVAILABLE SIZES

STANDARD THICKNESS 8m rolls

STANDARD ROLL SIZE 3mm x 3mm through to 25mm x 25mm

AVAILABLE STYLES Lubricated (L) or Pure

Cut lengths, strips and custom shapes are available upon request
Larger coils & sizes available upon request



APPLICATIONS

MP4130 may be used for pumps and valves in strong acid and alkali service petrochemical and refining. Suitable for a range of applications including:

- > Rotary
- > Reciprocating
- > Static

Care must be taken when using in Rotary service to avoid burning and glazing of packing on start up.



Sheet conforms to FDA
regulations 21 CFR
177.2600