



MP8007

Pure Graphite Tape | Valv-Pac | Corrugated or Smooth | With or Without Adhesive Backing

FEATURES

MP8007 (Valv-Pac) is a corrugated or smooth formed pure graphite tape. Available with or without adhesive backing for ease of installation. Valv-Pac is able to conform to some stuffing box irregularities, ie. Overalling and stretching. It offers excellent sealing capabilities under extreme conditions for longer equipment life and less maintenance.

TECHNICAL INFORMATION

Purity	99.95% Pure
Density	1.0 to 1.1g/cc
Sulphur Content	<1,000ppm
Leachable Chlorides	<50ppm
pH Value	0-14 (except strong oxidisers)
Max Temperature	-200°C to +300°C (non-oxidizing) -200°C to +500°C (oxidizing) -200°C to +650°C (steam)
Max Pressure	Up to 10,000psi (68,948Kpa)
Colour	Black
MSDS	Available upon request

AVAILABLE SIZES

STANDARD WIDTH 6.5mm, 12.5mm, 19mm, 25.4mm standard

STANDARD ROLL SIZE 15, 20 & 30 metres

AVAILABLE STYLES Corrugated or Smooth

SHELF LIFE
With adhesive: 36mths
Without adhesive: Indefinite

Cut lengths, strips and custom shapes are available upon request
 Other sizes available upon request



APPLICATIONS

Valv-Pac has no impregnates, binders, additives, oil or grease which could possibly leave the packing and reduce its volume or contaminate the process media. It is ideally suited to:

- > High pressure applications
- > High temperature applications

Valv-Pac is non-hardening, dimensionally stable and impervious to gases and fluids. Adhesive backed is also non contaminating.