

# **CHUTEX 40 RUBBER**

40 Duro | Wear Resistant | Natural Rubber

### **FEATURES**

Chutex 40 Rubber is a pink, premium grade, soft, flexible and highly elastic 40 Duro, wear resistant natural rubber sheet. It has excellent resistance to wet and dry fine particle sliding abrasion.

Chutex 40 will display resistance to some mild chemicals, including acids and alkalis used in mineral processing.

Chutex 40 has good physical properties including mechanical strength and cut and tear resistance. This makes it suitable for wear protection and sealing applications which require the rubber to be both flexible and compressible.

### **TECHNICAL INFORMATION**

Polymer	NR	
Colour	Pink with smooth back	
Specific Gravity	1.05	ASTM D297
Hardness	40° ± 5° Shore A	ASTM D2240
Abrasion	95mm³ (max) @ 5N	ASTM D5963
Tensile Strength	18 MPa (min)	ASTM D412
Elongation @ Break	550% (min)	ASTM D412
Tear Strength	60 N/mm (min)	ASTM D624
Temperature Range	-20°C to + 70°C	

#### **AVAILABLE SIZES**

STANDARD THICKNESS

	19mm, 25mm
STANDARD ROLL SIZE	1200mm x 10mtrs (1.5mm, 3mm, 4.5mm, 6mm) 1500mm x 10mtrs (9mm, 12mm, 16mm, 19mm, 25mm

1.5mm, 3mm, 4.5mm, 6mm, 9mm, 12mm, 16mm,

Cut lengths, strips and custom shapes are available upon request



## **APPLICATIONS**

Chutex 40 Rubber has been designed primarily for use as a flexible, wear resistant rubber sheet or seal. It's mainly used in abrasion applications in the mining and mineral processing industry but can be used for any general sealing applications. Typical applications include:

- > Chute lining
- > Premium Chutex skirting rubber
- > Wear curtains
- > Dust sealing curtains & skirts
- > Pipe repair bandage
- > Pipe wipers / drill rod seals
- > Dust deflectors
- > Vacuum blankets

It can also be used for other applications which require a flexible abrasion resistant rubber includina:

- > Loading socks
- > Transfer and joining sleeves
- > Variety of sealing applications