



SBR 60 Rubber Sheet

60 Duro | Moderate Abrasion & Impact Resistant | Styrene-Butadiene Rubber

FEATURES

Industrial Gaskets SBR 60 Rubber is a black, superior grade, 60 Duro Synthetic rubber sheet. It has good physical properties such as mechanical and tear strength and has moderate abrasion resistance making it suitable for general insulating or isolating and gasket sealing applications



TECHNICAL INFORMATION

Polymer	SBR	
Colour	Black	
Specific Gravity	1.35	ASTM D297
Hardness	65° ± 5° Shore A	ASTM D2240
Abrasion	300mm ³ (max) @ 10N	ASTM D5963
Tensile Strength	7 MPa (min)	ASTM D412
Elongation @ Break	350% (min)	ASTM D412
Compression Set	35%	ASTM D395 B
Tear Strength	60 N/mm (min)	ASTM D624
Temperature Range	-20°C to +70°C	

AVAILABLE SIZES

- **Standard Thickness - 0.8mm, 1.5mm, 3mm, 4.5mm, 6mm, 9mm, 12mm**
- **Standard Roll Size - 1200mm x 10mtrs**

APPLICATIONS

Industrial Gaskets SBR 60 Rubber Sheet has been designed primarily for use as a flexible strip, pad, lining or gasket and is mainly used for sealing, insulating, isolating and protecting steel or other surfaces. Its properties make it suitable for use in a wide range of applications including:

- >Flange gaskets on pipes and tanks
- >Insulating strip
- >Isolation barriers
- >Dust seals and covers
- >Variety of sealing applications



www.industrialgaskets.com.au

Whilst every effort has been made to supply accurate information this specification should be used as a guide only. IG reserves the right to make specification changes without notice or without incurring liability.

Industrial Gaskets | Sheet Rubber

E sales@industrialgaskets.com.au
P (08) 8276 4140